(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 12 July 2001 (12.07.2001)

PCT

(10) International Publication Number WO 01/50232 A2

(51) International Patent Classification7:

(21) International Application Number: PCT/IB00/01963

(22) International Filing Date:

22 December 2000 (22.12.2000)

(25) Filing Language:

English

G06F 1/16

(26) Publication Language:

English

(30) Priority Data:

09/474,447 29 December 1999 (29.12.1999) US
(71) Applicant: NOKIA CORPORATION [FI/FI]; Keilalah-

- dentie 4, FIN-02150 Espoo (FI).
- (71) Applicant (for LC only): NOKIA INC. [US/US]; 6000 Connection Drive, Irving, TX 75039 (US).
- (72) Inventors: ZHANG, Rui; 55 Griffen Drive, Scarborough, Ontario M1B 1A4 (CA). VAARIO, Jari; Hakusan 2-31-2-301, Bunkyo-Ku, Tokyo 112-0001 (JP).
- (74) Agent: STUART, Michael, C.; Cohen, Pontani, Lieberman & Pavane, Suite 1210, 551 Fifth Avenue, New York, NY 10176 (US).


- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

 Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: DISPLAY DEVICE



(57) Abstract: A display device comprising a stick-shaped housing holdable in one hand and a screen, made from cholestric liquid crystal material, extendable from the housing to provide a display for the user.



01/50232 A2

WO 01/50232 PCT/IB00/01963

Display Device

BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a display device.

2. Description of the Related Art

In known portable devices including displays,

10 a balance always has to be struck between portability
and usability. For example, currently, a notebook PC is
too big to be conveniently carried, although the display
is adequate. Whereas, a palmtop computer is small
enough to be carried unobtrusively, but the user has to

15 put up with a small display.

SUMMARY OF THE INVENTION

With this in mind, according to one aspect, the present invention may provide a display device comprising a stick-shaped housing holdable in one hand, and an electronically-writeable screen extendable from the housing to provide a display for the user.

In this way, the present invention is able to provide a display which is very convenient to transport, yet provides an adequate screen when needed.

Preferably, the display device includes a user control on the housing by which the user can adjust the degree to which the screen is extended.

This feature is advantageous in that it 30 enables the user to extend the screen of display device to the extent permitted by the circumstances, whereby the display device may be used in even very cramped situations such as on commuter trains.

20

Preferably, the display device comprises a window formed in the housing through which a portion of the screen material is viewable when in its first position. The visible portion of the display can then be used to display a limited amount of key information to the user, even when the display material is in its first position.

According to a further aspect of the invention, the present invention may provide a personal communication device comprising a display device as hereinbefore discussed and a radio interface.

Other objects and features of the present invention will become apparent from the following detailed description considered in conjunction with the accompanying drawings. It is to be understood, however, that the drawings are intended solely for purposes of illustration and not as a definition of the limits of the invention, for which reference should be made to the appended claims.

20

10

15

BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, wherein like reference numerals delineate similar elements throughout the several views:

- FIG. 1 shows an embodiment of the invention in the closed position;
 - FIG. 2 shows a longitudinal cross-section of the embodiment of FIG. 1;
- FIG. 3 shows a cross-sectional view of the 30 printed circuit board (PCB) shown in FIG. 2;
 - FIG. 4 shows a functional block diagram of electronic components of the FIG. 1 embodiment;
 - FIG. 5 shows the embodiment of FIG. 1 in a partly-opened position; and

5

10

15

20

25

FIGS. 6 and 7 show the embodiment of FIG. 1 in a fully-opened position.

DETAILED DESCRIPTION OF THE PRESENTLY PREFERRED EMBODIMENTS

Referring to FIG. 1, a personal communication device 10 of the present invention comprises a stick-shaped housing, generally designated 12, which is sized to be conveniently held in one hand. The housing 12 has a first end 12a and a second end 12b, and is provided longitudinally along the length thereof with a transparent window 14. At the first end 12a of the housing 12, a 5-position, roller-ball mouse 16, an 'open' button 18 and a 'close' button 20 are provided.

Referring to FIG. 2, within the housing 12 a hexagonal printed circuit board (PCB) 22 is mounted. inside surface of the PCB 12, the circuitry necessary to control the operation of the device is laid This circuitry 50 is closed from the volume surrounded by the PCB 12 by a component cover 23. Within the volume enclosed by the component cover 23, a battery 24 for powering the device is located. battery 24 is replaceable and can be removed from the second end 12b of the housing 12. Electronicallywriteable screen material 26 is rolled around the PCB 22. The display material 26 can be cholestric display material, including cholestric liquid crystals. A motor 28 is mounted at the first end 12a of the housing 12. The motor 28 is coupled to the screen material 26.

Referring to FIG. 4, the circuitry 50 comprises a radio interface 52, including an internal 30 antenna capable of both data reception and transmission; a motor driving unit 56 for driving the motor 28; a display driver 58 for writing to the screen material 26, example, in accordance with U.S. Patent for No. .

5,933,203, the disclosure of which is incorporated by reference; and a control unit coordinating the overall operation of the including directing the operation the radio interface 52, the motor driving unit 56 and the display driver 58. The control unit 60 is also responsive to the mouse 16, and open and close buttons 18 and 20, respectively.

Referring again to FIG. 1, the device 10 is in standby mode in which the screen 26 is fully scrolled-up within the housing and only a small portion of the screen, hereinafter referred to as the window display, is visible through the window 14. The window display shows key information to the user. In this instance, the time and the fact that the device has In the standby mode, the radio received new messages. interface 52 maintains contact with a cellular network and can accept incoming messages.

When the user wishes to make active use of the device 10, he might, for example on a commuter train, chose to unscroll the screen to only the extent shown in FIG. 5 because the train is crowded. He does this by the open button 18 for a predetermined depressing duration. The button depression is detected by the control unit 60. While the key is depressed, 25 control unit 60, via the motor controller 56, drives the motor 28, thereby causing the screen portions 26a and 26b to be steadily unscrolled from the housing 12 and extend laterally from the housing. Once the open button is released, the unscrolling terminates. The material of the display may have sufficient rigidity itself to maintain its planar form as it is being unscrolled. With some display materials this may not be the case, and the material can be provided with a thin metal backing which can be rolled and unrolled with the screen

10

15

20

to impart the necessary structural rigidity. The backing may take the form, for example, of a thin border running around the edges of the screen or a framework extending over the back of the screen. It will be noted that the height of the screen is less than that of the housing. The reason for this is to create a region at one end of the housing 12 by which the housing can be readily held by the user during the rolling out or rolling up of the screen without the screen interfering with the user's hands. The buttons 18, 20 and the mouse 16 are positioned proximate to this end region.

On the left-hand screen portion 26a, the user with a series of icons indicating the is presented various services the device 10 supports and can access over the air using its radio interface 52. As shown in FIG. 5, these include "newspaper", "internet", "email", "TV phone". By moving the screen cursor (not shown) using the mouse 16, the user is able to select the required service. The newspaper service accesses, over the air via the internet or via a dedicated server, the user's regular newspaper. On the right hand screen 26b, there is shown weather forecast information. The device 10 formats the data it is displaying according to the current extend to which the screen is unscrolled. is very much like a Microsoft's Windows application, but, of course, in this case the physical display area actually varies.

By depressing the open button 18, the screen 26 can be unraveled to its maximal size. FIGS. 6 and 7 show examples of the device displaying various items of content downloaded over the air from the internet.

The two screen portions 26a, 26b can operate depending on the application to act as a single large display or two independent displays.

10

15

20

25

When the user wishes to stop using the device, he depresses the open button 20 for a predetermined duration. The button depression is detected by the control unit 60. While the key is depressed, the control unit 60, via the motor controller 56, drives the motor 28, thereby causing the screen portions 26a and 26b to be steadily scrolled up and withdrawn into the housing 12.

It will be appreciated that the device is 10 particularly suited to downlink intensive applications where a decent-sized display is desirable. Because the device can be readily held by one hand, it is very useable in difficult environments. Yet at the same time, bècause the screen can be rolled unobtrusively into the housing, the 15 device is extremely portable.

Thus, while there have been shown and described and pointed out fundamental novel features of the present invention as applied to a preferred embodiment thereof, will be understood that various omissions substitutions and changes in the form and details of the devices illustrated, and in their operation, may be made by those skilled in the art without departing from the spirit of the present invention. For example, it is intended that expressly all combinations of elements and/or method steps which perform substantially the same function in substantially the same way to achieve the same results are within the scope of the invention. Substitutions of elements from one described embodiment to another are also fully intended contemplated. It is also to be understood that the drawings are not necessarily drawn to scale but that they are merely conceptual in nature. It is the intention,

20

25

therefore, to be limited only as indicated by the scope of the claims appended hereto.

BNSDOCID: <WO_____0150232A2_I_>

CLAIMS


- 1. A display device comprising:
- a stick-shaped housing holdable in one hand;
 and
- 5 an electronically-writeable screen extendable from the housing to provide a display for the user.
- The display device of claim 1, further comprising user control means by which the user can adjust the degree to which the screen is extended.
 - 3. The display device of claim 1, wherein the screen is extendable from a first position in which the screen is fully retracted within the housing, and a second position in which the screen is maximally extended from the housing.
- 4. The display device of claim 2, wherein the screen is extendable from a first position in which 20 the screen is fully retracted within the housing, and a second position in which the screen is maximally extended from the housing.
- 5. The display device of claim 3, wherein the screen comprises first and second screen portions which are extendable in opposite directions from the housing.
- 6. The display device of claim 4, wherein 30 the screen comprises first and second screen portions which are extendable in opposite directions from the housing.


- 7. The display device of claim 3, comprising a window formed in the housing through which a portion of the screen is viewable when in its first position.
- 8. The display device of claim 4, comprising a window formed in the housing through which a portion of the screen is viewable when in its first position.
- 9. The display device of claim 2, further 10 comprising motor responsive to the user control means for rolling out and rolling in the screen.
 - 10. The display device of claim 1, further comprising a circuit board means arranged concentrically around a major axis of the housing.
 - 11. The display device of claim 10, further comprising battery means contained within a volume defined by the circuit board means.

20


15

12. A personal radio device comprising the display device of claim 1, further comprising a radio transceiver located within the housing.






BNSDOCID: <WO_____0150232A2_I_>



BNSDOCID: <WO____0150232A2_I_>



Newspa...

Newspa...

Internet

The Three controls of the control of the control

BNSDOCID: <WO_____0150232A2_L>




FIG. 6

2008年五輪の大阪招数委が発足「カリーンに活動」 宣言

フ、h. 会に向け、国内外でのFRに乗り出す。 「ト 。 の国際オリンビック委員会(100)総

る。招談教徒選尾にあたり、「五輪悪動物」 あいかっにはった婦性を表し会明日 設立総会は委任状出席を含める委員ら称

480人が参加し、大阪市内のホテルで 午後5時過ぎかる関かれた。 会長に確村隆文市長、会長代行に断宮

。 阪オリンビック電影委員会」がも日、第一日本サリンビックを開建文大阪南田会議所、「OO」の古、「B、日本サリンビック電影委員会」がも日、第、日本サリンビック委員会(「OO)の古い。 8008年五輪の大阪開催を目指す「大、関西経済連合会会長を引は、「量で!」(の国際オリンビック委員会(100)総(会領やが就き、名害会長を提講明・10 O名言会長、特別語語を使出ノック・大 夏季五輪だ。しかし、100巻のぐる騒」として政府関係者をが当面の参加を見合実現すれば、東京に次ぎ日本で2度目の「阪府和事に委嘱した。100銭感を理由 の活動には世界の眠しい目が注がれ、 545人での「龍出」となった。(2.20mm)となった。(6.20mm)となった。(6.20mm)となった。(6.20mm)とはおおはいいます。 ひばいとして、今後、わせたことで、予定より105人かかい。 『19mm』であるます。 「たし、「ししきゃく?」

ルに従って海動することを暗聴した。

4割、経済界 4割、大阪府 2割の予算は30月までは6000の万円、市予算は30月までは600の万円、市 割合で負担する。


20:38 13 Jan 1999

Kou have 2 new messages









colorestR上高 り 兆円世界最大の企業に

接待総額300万ドル



BNSDOCID: <WO_ _0150232A2_I_>

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 12 July 2001 (12.07.2001)

PCT

(10) International Publication Number WO 01/50232 A3

(51) International Patent Classification7:

.....

(21) International Application Number: PCT/IB00/01963

(22) International Filing Date:

22 December 2000 (22.12.2000)

(25) Filing Language:

English

G06F 1/16

(26) Publication Language:

English

(30) Priority Data:

09/474,447


29 December 1999 (29.12.1999) US

- (71) Applicant: NOKIA CORPORATION [FI/FI]: Keilalahdentie 4. FlN-02150 Espoo (FI).
- (71) Applicant (for LC only): NOKIA INC. [US/US]; 6000 Connection Drive, Irving, TX 75039 (US).

- (72) Inventors: ZHANG, Rui; 55 Griffen Drive, Scarborough, Ontario M1B 1A4 (CA). VAARIO, Jari; Hakusan 2-31-2-301. Bunkyo-Ku, Tokyo 112-0001 (JP).
- (74) Agent: STUART, Michael, C.; Cohen, Pontani, Lieberman & Pavane, Suite 1210, 551 Fifth Avenue, New York, NY 10176 (US).
- (81) Designated States (national): AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL. SZ. TZ. UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,

[Continued on next page]

(54) Title: COLLAPSIBLE DISPLAY DEVICE



(57) Abstract: A display device comprising a stick-shaped housing holdable in one hand and a screen, made from cholestric liquid crystal material, extendable from the housing to provide a display for the user.

BNSDOCID: <WO_____0150232A3_I >

WO 01/50232 A3



IT. LU. MC, NL, PT, SE, TR). OAPI patent (BF, BJ, CF, CG, Cl, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

(88) Date of publication of the international search report: 27 December 2001

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

BNSDOCID: <WO____0150232A3_I_>

INTERNATIONAL SEARCH REPORT

Inte .ional Application No PCT/IB 00/01963

		[61/]	18 00/01963		
A. CLASS IPC 7	FIFICATION OF SUBJECT MATTER G06F 1/16				
According	to International Patent Classification (IPC) or to both national class	ification and IPC			
	SEARCHED				
IPC /	ocumentation searched (classification system followed by classific G 0 6 F				
	alion searched other than minimum documentation to the extent the				
	tata base consulted during the international search (name of data ternal, WPI Data, PAJ, IBM-TDB	base and, where practical, search ter	ms used)		
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT				
Category ·	Citation of document, with indication, where appropriate, of the	relevant passages	Relevant to claim No.		
Х	WO 98 03962 A (JUNKYARD DOGS LTD) 29 January 1998 (1998-01-29) page 14, line 3 -page 15, line 15 figures 12A,14,15		1-4,9		
Α	EP 0 424 074 A (FAILLA STEPHEN 3 24 April 1991 (1991-04-24) column 18, line 31 -column 20, 1 figures 46-52	1-4,9,12			
A	EP 0 776 140 A (NOKIA MOBILE PHO 28 May 1997 (1997-05-28) column 3, line 3 -column 5, line column 9, line 21-40 figures 4,5	1,12			
Furth	er documents are listed in the continuation of box C.	Y Patent family members are	e listed in annex.		
Patent family members are listed in annex. Special categories of cited documents: "T" tater document published after the international filling date					
A document defining the general state of the art which is not considered to be of particular relevance *E* earlier document but published on or after the international		or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention			
citation	nt which may throw doubts on priority claim(s) or s cited to establish the publication date of another or other special reason (as specified)	cannot be considered novel or involve an inventive step when "Y" document of particular relevance cannot be considered to involve	cannot be considered to the document is taken alone t; the claimed invention		
O document referring to an oral disclosure, use, exhibition or other means *P* document published prior to the international filling date but later than the priority date claimed		document is combined with one or more other such docu- ments, such combination being obvious to a person skilled in the art. *&* document member of the same patent family			
	ctual completion of the international search	Date of mailing of the internation			
5	July 2001	12/07/2001			
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2		Authorized officer			
NL – 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo ni, Fax: (+31-70) 340-3016		Baldan, M			

Form PCT/ISA/210 (second sheel) (July 1992)

INTERNATIONAL SEARCH REPORT

Information on patent family members

Intc .ional Application No PCT/IB 00/01963

Patent document cited in search report	t	Publication date	Patent family member(s)		Publication date 27-03-2001 03-05-2001 10-02-1998 06-05-1999
WO 9803962	A	29-01-1998	US 6205690 B AU 733071 B AU 3736397 A EP 0912972 A		
EP 0424074	Α	24-04-1991	US	5128662 A	07-07-1992
EP 0776140	Α	28-05-1997	FI JP US	955682 A 9181802 A 6047196 A	25-05-1997 11-07-1997 04-04-2000